# User Manua ITEM# 62009900 UMJOG06-22LITUS





BERGERON HEALTH CARE  $\mathsf{TM}$ 

# **Table of Contents**

Intended Use	3
Environment of Use	3
List of Parts Included and Optional Accessories	3
Important Warning Information	3
Cleaning & Maintenance	
Dimensions	
Assembly & Fitting	
Front Wheel Installation	
Front Wheel In-line Locking	7
Rear Wheel Installation	
Safety Harness	7
Rear Wheel Parking Brake	8
Reclining Seat	9
Removing Seat Fabric	
Shopping Basket	10
Canopy Installation	10
Handle Height	
• Folding	11
Attendant Strap	12
Optional Accessories	
Seat & Back Liners	
Head Rest	
Washing	. 13
Lifting	. 14
Limited Warranty	. 14

#### **Intended Use**

The Special Tomato Jogger Pushchair is a jogger that provides mild to moderate positioning support for children with special needs. Its large wheels and sturdy frame make it ideal for both smooth indoor surfaces and rugged outdoor trails. It offers typical features for a lightweight jogger, including several adjustment options, accessories, a brake mechanism, user safety tether and the ability to fold for easy transport. The EU version features a front wheel cable operated disk brake.

#### **Environment of Use**

The Jogger Push Chair is intended for both indoor and outdoor use, in the home and community. If used in the rain, wipe off excess water with a soft cloth. If the chair is splashed with mud or corrosive substances like road salt, the chair should be washed clean with water, wiped dry, and a hypoallergenic and biodegradable lubricant reapplied to the moving parts. Contact with seawater should be avoided, as it will corrode areas that cannot be washed clean. When going from outside to inside, clean any excess dirt or mud from the wheels to prevent soiling of inside environment.

↑ Warning: Avoid open flames\* and prolonged exposure to extreme heat or cold, including direct sunlight and saunas. Check temperature of chair before use.

### **List of Parts Included and Optional Accessories**

Parts Included

- 1 Folded Jogger Push Chair (pre-assembled)
- 1 Jogger Front Wheel, 2 Jogger Rear Wheels
- 1 Attendant Tether Strap

Optional Accessories

- Jogger Rain Cover
- Soft-Touch Seat and Back Liners
- Soft-Touch Sitter
- Medical Necessities Bag
- Jogger Head Support

#### **Important Warning Information**

Name was a serious injury from falling or sliding out. Always use the seat harness. Never leave child unattended.

- ↑ IMPORTANT: Keep these instructions for future reference and follow all instructions carefully. A child's safety is your responsibility. This jogger is suitable for one child. Always use the attendant strap while jogger is occupied by a child. Maximum weight for this jogger is 110lbs or 50 kg.
- exercise.
- Children should be harnessed in at all times and should never be left unattended. The harness and seat belt are not a substitute for proper adult supervision
- It is important for your child's safety that the harness be correctly fitted and adjusted. If not adjusted correctly in accordance with the instructions, the stability of the Jogger will be compromised.
- Never leave child in the Jogger when ascending or descending stairs or escalators or when travelling on other forms of transport.
- Apply brake when parking the Jogger.

- Front wheel must be kept in-line for Do not carry additional children, goods or accessories in or on this push chair except as permitted in this manual. They may cause the Jogger to become unstable or place unneeded stress on the Jogger that could lead to breakage.
  - Overloading, incorrect folding and the use of accessories, e.g. child seats, bag hooks, rain covers, buggy boards, etc., other than those approved by the manufacturer may damage or break this Jogger.
  - Any damage caused by the use of accessories not supplied by manufacturer will not be covered by the terms of our warranty.
  - Never allow children to stand on the footrest.

- The Jogger should always open and fold easily. Do not force it. It may be necessary to re-read the instructions.
- Negotiate curbs and rough ground carefully. Repeated impact will cause damage to the push chair.
- Do not place items on the top of the hood as it may cause damage to the canopy.
- The child should be clear of moving parts while making adjustments. It is important that care is taken to ensure that children are kept clear of the Jogger when folding or unfolding. Pinch points and scissoring actions are unavoidable during these operations

#### **Cleaning & Maintenance**

#### Cleaning

- Clean frame with a damp cloth and a mild detergent and dry thoroughly.
- The canopy may be sponged lightly using a damp cloth and a mild detergent. The seat cover, head cushion, lateral pads and harness pads may be washed. Line dry thoroughly before reuse. Gray Harness can be placed in a mesh bag and machine washed on gentle cycle only.
- Do not fold or store the product while wet and never store in a damp environment; this can cause mildew to form.
- You can machine wash the Jogger seat fabric in cold water with a mild detergent. To minimize shrinkage, simply reattach the seat fabric to the frame to dry. (DO NOT put seat in the dryer)
- Be sure to unzip and remove all three rigid board from the seat before washing.

#### **Maintenance**

This Wheelchair requires regular maintenance by the user. Before each use, check all rivets and connecting devices for tightness and security. Inspect all brakes, wheels, and tires and replace or repair if necessary. Check all safety devices for correct operation. Never continue to use a product that is not structurally sound. The following maintenance procedures should be conducted on a regular basis:

- Tire air pressure should be checked weekly, since low air pressure may affect brake ability.
- Axles and moving parts should be wiped off weekly
  with a slightly moist cloth to remove dust, dirt and mud.
  Sparingly apply a high quality Teflon spray after each
  cleaning. DO NOT USE WD-40, silicone sprays or other
  lubricant sprays as they will attract dust and dirt.
- In the event of a flat tire, remove wheel from frame, remove tire & inner tube from rim and patch hole using standard bicycle repair kit.
- Repair or replace loose, worn, bent, missing or damaged parts before using the chair. Only manufacturer replacement parts should be used. It may be unsafe to use parts not supplied by manufacturer.

Maintenance Chart	Weekly	Every 3 months	Every 6 months	As necessary
Rims, tires, and tire pressure	•			
Wheel locks and hand brakes	•			
Accessories	•			
Front and rear wheel axles	•			
Cleaning/lubricating all moving parts <sup>1</sup>	•			
Belts, zippers, and hook-and-loop closures		•		
Seat/back upholstery <sup>2</sup> and tautness		•		
Armrests & foam			•	
Frame			•	
Contacting a Special Tomato dealer for service or repair <sup>3</sup>				•

<sup>1</sup> Note: Do NOT use WD-40 or other silicone-based spray as a lubricant. 2 Follow cleaning instructions for appropriate user hygiene

<sup>&</sup>lt;sup>3</sup>Note: Repair or replacement of non-removable, worn, or broken parts must be performed by a qualified service facility.

# **Dimensions**

Jogger Sizing Chart	Dimensions		
Maximum Weight Capacity	110 lbs. (50 kg)		
Seat Width	14 (35 cm)		
Seat Depth	12" (30 cm)		
Crotch Strap Depth from Seat Back	7.5 or 11.5" (19 or 29.2 cm)		
Seat Back Height	25" (62.5 cm)		
Shoulder Strap Height	11, 14 or 17" (28 35.6 or 43.2 cm)		
Seat to Footwell	15" (37.5 cm)		
Handle Height to Floor	35" - 43" (87.5 - 107.5 cm)		
Seat Recline Range	100-140°		
Overall Dimensions (width x length x height)	26" x 42" x 43" (65 x 105 x 107.5 cm)		
Weight of Jogger	27 lbs. (12 kg)		
Folded Dimensions (w/o rear wheels)	33" x 21" x 16" (82.5 x 52.5 x 40 cm)		
Manufacture Date Code			

Note: Serial # located on inner metal frame near rear tire.

#### Assembly & Fitting (Unpack Jogger from Box and set wheels aside)



1. Push foot plate of Jogger away from handle by pushing curved crossbar up and out.



2. Audible click will be heard when Jogger frame is completely unfolded.



3. Flip Jogger to upright position and clip lower belting around frame to secure seat fabric.


**Note:** Check our YouTube channel for instructive and informative videos!

#### **Front Wheel Installation**



Lay Jogger on its back with handle and rear axle are touching the floor.

5. Place red Safety Retainers onto each side of the wheel axle as shown, then slide the front-wheel into the front-fork slots.



6a. Install M5 bolt and washer through fork into the threaded hole on red Safety Retainer as shown. Repeat on opposite side with second M5 bolt and washer.

6b. Insert skewer through wheel and install black skewer nut. Tighten by turning the skewer lever.



6c. Close the skewer lever making sure that it is flush with the tubing. Be sure not to over tighten.







Pull and rotate knob to lock and unlock. unlock. Image shows unlocked.

7. The in-line locking mechanism is 8. Image now shows the wheel locked located behind the front wheel pivot point. in-line. Pull and rotate mechanism to

#### **Rear Wheel Installation**




9. To install, gently slide the rear wheel's 10. To remove, simply push down the axle into the frame's supporting axle hole spring lock tab while pulling out on the until you hear it click into place.



wheel.

## **Safety Harness**





11a. To adjust Safety Harness, unclip hooks.

11b. Remove fleece lining by lifting Velcro tabs as shown.

# Safety Harness (continued)



12. Unthread harness straps from fleece lining.



13a. Insert shoulder straps through loops for desired shoulder height.

13b. Fine tune strap length for secure fit.



14a. Clip shoulder strap buckle to chest 14b. To adjust the length of the center harness.




strap, move the plastic guide up and


For additional instruction, refer to video guide found at this link: bit.ly/ JP6X482

NOTE: Once fitting is complete, reassemble the fleece lining.

#### **Rear Wheel Parking Brake**




15. To apply the parking brake, press down on the foot bar.



16. To disengage the brake, pull up on the foot bar.

#### **Reclining Seat**




to desired degree of recline.




17. Simply adjust the recline strap length 18. Unlock the buckle shown in Figure 17 for maximum recline.

## **Removing Seat Fabric**



19. Using a Phillips head screw driver 20. Unsnap fasteners on both sides of unscrew hardware from the frame.



jogger.



20a. Unlock seat strap from frame, buckle is suspended across the back of the jogger.




21. Unloop Velcro Strap through the D-ring, underneath the foot well.

#### NOTE: REMOVEALLRIGID PARTS BEFORE WASHING

Joggers are shipped with Seat pre-assembled. Assembly/Removal instructions are given if any preassembly items are removed for cleaning or replacement, refer to page 8 for additional information.

#### **Shopping Basket** (optional)



22. Secure front basket flap by snapping around the lower foot-well crossbar.

22a. Detail of front shopping basket snaps.




23. Wrap rear basket straps around the frame and loop back through the D-ring. Secure the Velcro strap.

NOTE: The D-ring loops are at the rear of the basket.


#### **Canopy Installation**






22a

24a. Fasten the canopy to the portion 24b. Hook the wire of the upper frame that is not covered the canopy mechal by fabric. Small holes in the crest of the lever by pressing the frame tubing accept the canopy. Be NOT FORCE TO C sure there are NO obstructions between for obstructions and the canopy clip and the frame. There is a small plastic nipple on the canopy mechanism that fits into the hole in the frame.



24b. Hook the wire on the back side of the canopy mechanism and then close the lever by pressing it to the frame. DO NOT FORCE TO CLOSE! Double check for obstructions and be sure nipple is inserted into frame.

## **Handle Height**



25. Adjust handle height, then re-lock.



25a. Adjust handle height, then re-lock.

# **Folding**

To ease Jogger Folding:

- Fully recline seat back
- Disengage Velcro Between Canopy
   & Seat Back
- Push handle all the way up
- Unlock front wheel swivel lock
- Undo 5 point harness



NOTE:

Folding

mechanism appears on

both sides.

26. Squeeze folding mechanism located below the handle.



26a. Fold jogger back.



26b. Secure Jogger in folded position with recline strap.

#### **Attendant Strap**



27. Make sure safety wrist strap is secured properly around your wrist whenever your child is in the jogger.

### **Optional Accessories: Seat & Back Liners**









28. Using the provided straps with the Seat & Back Liners, feed the straps through the slots in Jogger seat & back.

28a. Place the Back Liner Straps into the slot at the height where you want the laterals will provide support.

28b. The Seat Liner Straps will go through the lowest slots.

28c. Clip the straps for both the Seat & Back Liners to each other on the back side of the jogger and tighten until secure.

NOTE: The Jogger Chest Harness should lay over the top of the Back Liner for correct positioning. The Jogger 3-Point lap belt can be fed through the 3 holes of the Seat Liner for optional positioning.

#### **Optional Accessories: Head Rest**



29a. Use the strap provided with the 29b. Optional Head Rest to secure it to the through the slots on the on the back side of the Jogger Jogger.



Thread the Jogger.




straps 29c. Clip the straps together and tighten to secure it.

#### **Washing**







30. You can machine wash your Jogger seat in cold water with a mild detergent. To minimize shrinkage, simply reattach the seat to the frame to dry. Be sure to remove all THREE (3) the rigid boards from the upholstery before washing. Unzip all THREE (3) zippers to remove the rigid boards.

30a Rigid Board #1

30b Rigid Board #2

30c Rigid Board #3

NOTE: Do NOT put seat in the dryer. You may clean the Jogger frame using a soft, dry cloth.

#### Lifting



WARNING: Never lift the push chair with a child in it.

To lift the push chair, firmly grasp the plastic portion of the front tube frame beneath cross section on **both** sides of Jogger.



### **Limited Warranty**

Your push chair is guaranteed to be free from any manufacturing defects for a period of 2 years from the date of purchase under normal use and provided it is used in compliance with the operating instructions. This warranty extends only to the original retail purchaser and is only valid when supplied with proof of purchase. Please retain proof of purchase with this Limited Warranty.

Should a repair be needed please contact the retailer from whom the product was purchased. Please note that the warranty will not be applicable if:

- A fault is caused by misuse or poor maintenance.
- Repairs are carried out by a third party.
- The Jogger is faulty due to general wear and tear which is the result of everyday use.
- The Jogger is damaged as a result of an accident.
- ■The manufacturer is not satisfied that the stated warranty terms and conditions have been met.



Bergeron Health Care 22 South Second Street Dolgeville, NY 13329



Global Carehab HOLMSTRUPGAARDVEJ 11 8220 BRABRAND DENMARK +45 24 65 55 50



International: 1-315-429-8407 Fax: 1-315-429-8862

© 2022 Bergeron Health Care The information contained herein is subject to change without notice.